Chatillon®
force measurement

ForceTest™
# Force & Torque Testing Software

Overview

A   **Test Readings**   The Test Readings are enabled when a test run is finished. The Test Reading table shows the raw readings from a test run with a time stamp. Test Readings is hidden by default; pressing the Readings label will display the Test Readings table.

The Test Readings change to the readings for the test run selected in the Test Record table.

B   **Test Setup**   Configuring ForceTest and setting up tests is handled by the tabs in the ForceTest ribbon.

C   **Test Records Table**   The Test Records table displays the runs already performed for a loaded test. By default, the test record displays the Status, SNo, Color, Started on, Direction, and Note fields. When results are selected, the table will grow to include the results as well.

D   **Graph**   The graph plots a running test run or the test run selected in the Test Record table. Once a test run is finished, the graph can be zoomed in and out using the CTRL key on the keyboard and a mouse wheel. When multiple test runs are selected in the Test Record table, the graph will overlay test runs to allow comparison between test runs.

E   **Test Control Panel**   Live display, Zero, and Start/Stop controls.

F   **Live Display**   The Live Display shows the current reading from a connected gauge in the unit defined in the Live Display group on the Preference tab. This can be different from what is configured and displayed on the gauge.

G   **Zero**   Pressing the Zero button will zero a connected gauge.

H   **Start/Stop**   The Start and Stop buttons are enabled if a gauge is connected. A new test run is started by clicking the Start button and stopped by clicking the Stop button. When a test starts, ForceTest records the data points from the gauge and plots them in real-time. Additionally, a test run can be controlled via the keyboard. The F5 key will start a test run and the F7 key will stop it.

Specifications

Chatillon® ForceTest is a Microsoft Windows™ based data analysis package for Chatillon DF II and DF I Series gauges. This software is designed to enhance the capabilities of your force gauge by allowing you to record and analyze data on your computer. ForceTest can be used to test, acquire data and analyse results for:

▶ Pull to Break testing

▶ Pull to Limit testing

▶ Compress to Rupture testing

▶ Compress to limit testing

▶ Friction testing

▶ Peel testing

▶ Torque testing

System Requirements

Operating System Requirements

The following Microsoft Windows operating systems are supported:

▶ Microsoft Windows 7 SP1

▶ Microsoft Windows 8.1

▶ Microsoft Windows 10

Software Requirements

ForceTest requires the following dependencies be installed to operate. If they are not installed, the Force-Test installer will install them during the ForceTest installation.

▶ Microsoft NET 4.5.2

▶ Microsoft Report Viewer 2010 SP1

Minimum Hardware Requirements

The following minimum computer requirements are required to run ForceTest:

▶ 1 gigahertz (GHz) 32-bit (x86) or 64-bit (x64) processor

▶ 1 gigabyte (GB) RAM (32-bit) or 2 GB RAM (64-bit)

▶ 2 GB available hard disk space

▶ 1024 by 768 px display

▶ 1 USB port or RS232 port (RS232 port requires the SPK-DF-RS232 cable)

▶ Chatillon DF I Series or DF II Series Force Gauge

◀ Easy Export and Reporting

Test results are presented in a spreadsheet format allowing you to analyze data and perform common mathematical and statistical calculations.

Results may be displayed graphically versus time. Tabular results are displayed and can be used to create relationships, queries or used to produce reports. Test results can be exported to a .csv format. Graphs and test results can also be exported directly to PDF and Word formats.

AMETEK®
SENSORS, TEST & CALIBRATION

For detailed specifications
go to the Data Sheet at ametektest.com

Chatillon®
force measurement

AMETEK®
SENSORS, TEST & CALIBRATION