function

The **SCITEQ** Charpy pendulum impact tester is used to conduct resilience tests on rigid plastic materials in order to determine their impact fragility characteristics under standard stress conditions. The test method conforms to ISO 179 - Part 1 (non-instrumented impact test).

highlights



features

The **SCITEQ Charpy** pendulum impact tester is easy to operate with its simple and to-the-point menu structure. The test specimen can be cut by means of a copy milling machine.

The test specimen, supported near its ends as a horizontal beam, is impacted by a single blow of a striker, with the line of impact midway between the supports, and bent at a high, nominally constant, velocity.



We wish to give our partners the tools to produce to the highest standard, while helping them to produce as cost effectively as possible with Q.C. tools throughout the factory.

construction

The **SCITEQ Charpy** pendulum impact tester has a frame made from steel and consists of a rotation shaft and a pendulum stop unit. In addition there is an anvil a level meter, a control panel, three feet and an eyebolt.

Further, a specimen support is supplied along with a centering device is supplied for notched Charpy specimens.

The pendulum either has a capacity of either 7,5/15 Joule or 25/50 Joule.

On the LCD display the absorbed energy in joules after test specimen impact will be shown. Recorded test results can be analysed further via equations specified in the standard.




LCD control panel with operating buttons

associated | equipment

🖌 🖌 essential equipment


copy milling machine

version 06/2010




display LCD

weight 108 kg



▲ essential equipment

force applied by means of the Charpy testing method



Charpy pendulum hammer

SCITEQ A/S

Rho 3 DK-8382 Hinnerup Denmark Tel: +45 86 96 19 33 Fax: +45 86 96 24 75 www.sciteq.com sales(at)sciteq.com

associated | equipment

copy milling machine

SCITEQ — A Brand of Quality